

Thank you so much for your order!

Product Care Guides can be found [online here](#).

If you have any questions or feedback, please get in touch:

hello@stitchandrivet.co.uk

www.stitchandrivet.co.uk



New Defender Seat Cover Fitting Instructions

Second Row 40/20/40 for 7 seaters

Move seats backwards / forwards and fold up / down as necessary throughout the process for ease of fitting.

Start with 40 side (Drivers Side)

1. Cap on seat base around the front, ease the bound side panel along between this seat base and the centre seat base.
2. Work the fabric towards the backrest and ease the rubber trim underneath the metal ISO fix plate (push into the foam to give yourself a little bit of space).
3. Remove the outer back panel at Velcro strips and cap the inner back around the back rest, ease the fly strip through the bottom of inner back (release the back rest lever to allow you to get through)
4. Secure the top & sides to the outer back panel with Velcro and the bottom fly strip along the bottom.

Passenger Side

5. Fit the 40 back as steps number 3 & 4 above.

Centre Seat & Bolster:

6. Remove outer back panel at Velcro strips & leave aside for now.
7. Rest seat base cover in place but you will need it to move for now.
8. Fit the bolster cover and secure rubber trim at base of this (the existing plastic moves to allow this)
9. Ease the fly strip through the bottom of inner back (release the back rest lever to allow you to get through)
10. Work the seat base fabric towards the backrest and ease the rubber trim underneath the metal ISO fix plate push into the foam to give yourself a little bit of space.

11. Then ease the bound side panel down between this seat base and the 40 seat base.
12. Work fabric towards the front of the seat base and cap in place with the elastic.

Back to the backrest....

13. Cap the inner back over the back rest (release the back rest lever to allow you to get around)
14. Secure the sides to the outer back panel with Velcro and the bottom fly strip along the bottom.

Head Rests

**Please note cut outs are always on the left-hand side as sitting*

15. Release Velcro, ease the cover over, press into the foam as you are working if required.
16. Flip the head rest down.
17. Secure with Velcro.

Note: Our seat covers are tailored to fit each seat snugly and are not designed to be removed and refitted regularly.

Seat covers are fitted at your own risk. Stitch & Rivet (a division of BI Engineering) takes no responsibility for any impairment of vehicle safety features caused by seat cover fittings. Warning: The plastic carrier containing this product is not a toy. To avoid danger of suffocation, keep out of reach of babies and children.