

Thank you so much for your order!

Product Care Guides can be found [online here](#).

If you have any questions or feedback, please get in touch:

hello@stitchandrivet.co.uk

www.stitchandrivet.co.uk



New Defender 90 5 seater Seat Cover Fitting Instructions

Driver and Front Passenger Seats

Main Seat

1. For ease of fitting:
 - a. Lift seat position and raise back rest.
 - b. At base of each seat, undo the clips (in forward pushing motion) to release the lower carpet backing.
2. Open zips along airbag side.
3. Cap on the seat base at the front of the seat, then work the fabric up towards back rest and fit the elasticated loop around belt buckle.
4. Ease the fly trim with squeeze buckles into the back of seat (push down onto the foam to help ease it and be careful of your nails)
5. Pull back of cover around to back of seat.
6. Work the fabric up onto back panel into the curves, adjusting to remove wrinkles as you go.
7. When cover is sitting nicely; close the zip.
8. Secure seat base strap to the outer back panel and adjust the straps accordingly.

Head Rest

**Please note there is a 'FRONT' label sewn into the Velcro on the front side of the headrest cover.*

1. Ease cover over head rest (note the front and back of the cover based on the faced opening).
2. Secure Velcro at base of head rest cover.

Note: Our seat covers are tailored to fit each seat snugly and are not designed to be removed and refitted regularly.

Seat covers are fitted at your own risk. Stitch & Rivet (a division of BI Engineering) takes no responsibility for any impairment of vehicle safety features caused by seat cover fittings.

Warning: The plastic carrier containing this product is not a toy. To avoid danger of suffocation, keep out of reach of babies and children.