

Thank you so much for your order!

Product Care Guides can be found [online here](#).

If you have any questions or feedback, please get in touch:

hello@stitchandrivet.co.uk

www.stitchandrivet.co.uk



New Defender

Seat Cover Fitting Instructions

Second Row 40/20/40 for 5 seaters

Move seats backwards / forwards and fold up / down as necessary throughout the process for ease of fitting.

Covers are packed ready for fitting with each seat & headrest tucked inside its back panel. For the centre back the armrest cover & headrest are inside it (seat base is joined to the passenger's side seat).

Start with 40 side (Drivers Side)

1. Pull on leather tabs at back of seat base to release the seat & flip base up. Cap on seat base cover around the front, ensure the straps are free to pass under the seat base. Ease the inner side panel along between this seat base and the centre seat base.
2. Work the fabric backwards and flip the straps under the seat base and attach to front buckles. Leave the buckles loose to ensure they have room to tighten when seat is clipped back in place over the raised car floor (adjust as necessary).
3. Keep seat base folded up for now.
4. Remove the outer back panel at Velcro strips & cap the inner back around the back rest, ease the fly strip through the bottom of inner back (release the back rest lever to allow you to get through). The cover allows access to ISO Fix Bars.
5. Secure the outer back panel to inner back at the bottom fly strip first, then sides & along the top.

Passenger Side

6. Fit the 40 seat & back as steps number 3 & 4 above.

Centre Seat & Bolster:

7. Flip armrest down. Remove Velcro for armrest cover, ease the cover over, press into the foam as you are working if required. Secure with Velcro. Keep the armrest down for next step.
8. Remove outer back panel at Velcro strips & leave aside for now.

9. Thread the inner backrest panel through behind the armrest from top to bottom. Cap the inner back over the back rest (release the back rest lever to allow you to get around)
10. Thread the bottom fly under backrest & attach to outer back panel at Velcro points.

Head Rests

**Please note cut outs are always on the left-hand side as sitting.*

11. Release Velcro, ease the cover over, press into the foam as you are working if required.
12. Flip the head rest down.
13. Secure with Velcro.

Note: Our seat covers are tailored to fit each seat snugly and are not designed to be removed and refitted regularly.

Seat covers are fitted at your own risk. Stitch & Rivet (a division of BI Engineering) takes no responsibility for any impairment of vehicle safety features caused by seat cover fittings. Warning: The plastic carrier containing this product is not a toy. To avoid danger of suffocation, keep out of reach of babies and children.